

AVA시리즈 (수분제거 유닛)

AVA

KA300AVA

KA600AVA

KA900AVA

KA2000AVA

KA4000AVA



재질 : 알루미늄

드레인타입 : 자동 드레인 방식

최대 허용 압력 : 16 bar

수분제거율 : 99.9999%

상품코드	에어 흐름양					에어손실 (7 bar) 기준	수분저장 (cc/ml)	인입구 배출구 (BSPT)	드레인 배출구 (BSPT)	파티클 제거 (Micron)	상품치수 (mm)		무게 (Kgs)
	CFM	L/sec	L/min	M ³ /min	M ³ /hour						너비	높이	
KA300AVA	10.6	5	300	0.3	18	0.38	250	1/2"	1/8"	1.0	ø60.5	242	0.48
KA600AVA	21.2	10	600	0.6	36	0.38	260	3/4"	1/8"	1.0	ø60.5	282	0.56
KA900AVA	31.8	15	900	0.9	54	0.38	270	3/4"	1/8"	1.0	ø60.5	322	0.66
KA2000AVA	70.6	33	2000	2.0	120	0.38	450	1"	1/8"	1.0	ø90	415	1.36
KA4000AVA	127	60	3600	3.6	216	0.38	420	1"	1/8"	2.0	ø90	485	1.68

에어 압력에 따른 허용범위

라인 압력 (psig)	14.5	29.0	43.5	58.0	72.5	87.0	101.5	116.0	130.5	145.0	159.5	174.0	188.5	203.1	217.6
라인 압력 (barg)	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15
허용 범위	0.53	0.63	0.73	0.79	0.87	0.94	1.00	1.09	1.17	1.25	1.33	1.40	1.48	1.56	1.64